



### Model SP-8

Single blade, single hydraulic conveyor motor,  
 Converts left or right side spreading  
 Width: 11ft. 8in. Weight: 18,500 lbs.

### Model SPD-8

SWITCH FROM RIGHT TO LEFT IN MINUTES!  
 Two blades right and left, and grade, slope, extend cylinders  
 Dual conveyor drive, right to left with the flip of a switch  
 Two variable height hopper discharge gates  
 Width: 12ft. 4in. (11ft. 2in. For Transport) Weight: 19,260 lbs.

## SPECIFICATIONS

### DIMENSIONS -

LENGTH: 19ft. (5.8m)  
 WIDTH: 11ft. 2in. (3.40m)  
 \* For Transport  
 HEIGHT: 7ft. 10in. (2.38)  
 WEIGHT: SEE ABOVE  
 WHEEL BASE: 110in. (279cm)

### ENGINE -

JOHN DEERE 4039D diesel,  
 80hp.@ 2500 rpm.  
 Hydrostatic Traction Drive,  
 Two Speed Trans.- LOW: 0-150 ft/min (46m/min),  
 TRAVEL: 0-11 mph (18km/hr)  
 Front Wheel Drive and Front Wheel Steering,  
 2 (front) 425/65r22.5 and 2 (rear) 11R22.5 TIRES

### CONVEYOR -

Left or Right side Discharge,  
 Roller Chain driven, heat and oil resistant Belt.  
 Variable speed Hydraulic Drive  
 0 to 450 ft/min. (137m/min)  
 Hopper: 3 cu.yd. (2.3 cu.m),

### BLADE -

Modular sections with a curved profile,  
 18in. (46cm) tall.  
 SPREAD WIDTH: 8ft. (2.44m) max.  
 4ft.(1.22m) fixed blade with a  
 2 to 4ft. hyd. extend section.  
 Hydraulic Grade and Slope:  
 12in. (30.5cm) above to 12in. below grade.  
 Adjustable Outer Edger Plate,  
 Flexible Inside Edger Flap  
 Variable length blade Push Tube  
 with Blade Stabilizer Brace

### CONTROLS -

All Drive, Steering, Brake and Spreading  
 functions are within easy reach.  
 Movable Control Station and Seat  
 for Left hand or Right hand operation.  
 Locking Panel Covers and Tool Box

### PUSH ROLLERS -

Self cleaning, pivoting, with  
 extendable frame to 14in. (35cm)



12in. above to 12in. below grade and + or - slope position.



MODULAR, CURVED PROFILE BLADE with the 2 - 4ft. EXTENDIBLE SECTION moves material out to 8ft. with smooth flow



FRONT WHEEL DRIVE and STEERING easily handles heavy loads, even up hill.



Movable CONTROL STATION includes all machine functions and positions for all options.



ROLLER CHAIN DRIVEN, HEAT AND OIL RESISTANT CONVEYOR With FLEXIBLE ROAD EDGE MATERIAL STOP



SPD spreading with LEFT HAND BLADE, after a QUICK change over from the right side.



TRENCH FILL OPTION



10' BROOM OPTION

**OPTIONAL FEATURES:**

- Trench fill Strike-off Box: levels material down to 34 in. below grade.
- Electronic Joint Match: AGL Sonic Ski and EZ-Pave controller
- Electronic Slope Control: AGL Slope Sensor and EZ-Pave controller
- Truck Hitch with hopper extension
- Broom Attachment: Sweepster - 32 in. dia X 10 ft.
- Hydraulically extending Push Rollers
- Washdown System: electric pump, 20 ft hose/reel and nozzle
- Lighting Package: head and tail lights and warning beacon